











| Model | Thread | | | | Length | Shape | Head | Diameters | | | Bladed | | Angle | Gauges | Color | | | | Weight | E-Bike | | | |
|---|--------------|------------------------------------|------------------------------------|-------------------------------------|-----------|-------|------|----------------------------|------------|---------------|----------------|--------|-------|--------|---------------------|-----------------|-----------------|-----------------|--------|--------|------------|----------------|--------|
| | Product name | 1.8 mm FG 2.0 Thread (DIN 79012) | 2.0 mm FG 2.3 Thread (DIN 79012) | 2.34 mm FG 2.6 Thread (DIN 79012) | | | | Length of thread 9 – 10 mm | Range [mm] | Double butted | Tripple butted | Bladed | | | Height of head [mm] | Diameter 1 [mm] | Diameter 2 [mm] | Diameter 3 [mm] | | | Width [mm] | Thickness [mm] | 90-95° |
|  DT champion® | • | | | • | 140 – 315 | | | | 6 | 1.8 | 1.8 | 1.8 | | | • | 15 | • | | | | | 359 | |
|  DT champion® | | • | | • | 140 – 315 | | | | 6.2 | 2 | 2 | 2 | | | • | 14 | • | • | | | | 444 | |
|  DT champion® | | | • | • | 140 – 315 | | | | 7.8 | 2.34 | 2.34 | 2.34 | | | • | 13 | • | | | | | 591 | • |
|  DT champion® straightpull | | • | | • | 140 – 315 | | | | | 2 | 2 | 2 | | | | 14 | • | • | | | | 440 | |
|  DT competition® | • | | | • | 238 – 300 | • | | | 6 | 1.8 | 1.6 | 1.8 | | | • | 15 16 15 | • | | | | | 311 | |
|  DT competition® | | • | | • | 238 – 300 | • | | | 6.2 | 2 | 1.8 | 2 | | | • | 14 15 14 | • | • | • | • | | 382 | |
|  DT competition® straightpull | | • | | • | 238 – 300 | • | | | | 2 | 1.8 | 2 | | | | 14 15 14 | • | • | | | | 378 | |
|  DT competition® race | | • | | • | 238 – 300 | • | | | 6.2 | 2 | 1.6 | 2 | | | • | 14 16 14 | • | • | | | | 312 | |
|  DT competition® race straightpull | | • | | • | 238 – 300 | • | | | | 2 | 1.6 | 2 | | | | 14 16 14 | • | • | | | | 308 | |
|  DT super comp® | • | | | • | 247 – 308 | | • | | 6.2 | 1.8 | 1.7 | 2 | | | • | | • | • | | | | 318 | |
|  DT revolution® | | • | | • | 247 – 308 | • | | | 6.2 | 2 | 1.5 | 2 | | | • | 14 17 14 | • | • | | | | 283 | |
|  DT alpine® | | • | | • | 260 – 305 | • | | | 7.8 | 2 | 2.34 | 2.34 | | | • | 14 13 | • | • | | | | 586 | • |
|  DT alpine III® | | • | | • | 260 – 305 | | • | | 7.8 | 2 | 1.8 | 2.34 | | | • | 14 15 13 | • | • | | | | 418 | • |
|  DT aerolite® | | • | | • | 238 – 300 | • | • | | 6.2 | 2 | | 2 | 2.3 | 0.9 | • | | • | • | • | • | | 278 | |
|  DT aerolite® straightpull | | • | | • | 238 – 300 | • | • | | | 2 | | 2 | 2.3 | 0.9 | | | • | • | | | | 274 | |
|  DT aero speed® | • | | | • | 215 – 305 | | • | | 6 | 1.8 | | 1.8 | 2.3 | 1.2 | • | | • | • | | | | 355 | |
|  DT new aero® | | • | | • | 215 – 305 | | • | | 6.2 | 2 | | 2 | 3.3 | 1.1 | • | | • | • | | | | 437 | |
|  DT aero comp® | | • | | • | 238 – 300 | • | • | | 6.2 | 2 | | 2 | 2.3 | 1.2 | • | | • | • | | | | 380 | |
|  DT aero comp® straightpull | | • | | • | 238 – 300 | • | • | | | 2 | | 2 | 2.3 | 1.2 | | | • | • | | | | 376 | |

• = Standard